

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 August 2005 (11.08.2005)

PCT

(10) International Publication Number
WO 2005/072640 A1

(51) International Patent Classification⁷: **A61C 8/00**

(21) International Application Number:
PCT/US2005/002717

(22) International Filing Date: 28 January 2005 (28.01.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/539,633 28 January 2004 (28.01.2004) US
11/035,266 12 January 2005 (12.01.2005) US

(71) Applicant and

(72) Inventor: **CANTER, Stanton, R.** [US/US]; 19274
Berclair Lane, Tarzana, CA 91356 (US).

(74) Agents: **HENRY, James, A.** et al.; Blakely, Sokoloff,
Taylor & Zafman, 12400 Wilshire Blvd., 7th Floor, Los
Angeles, CA 90025-1026 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance
Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: **ANCHORING ELEMENT FOR USE IN BONE**



(57) Abstract: An anchoring element for use in bone has a proximal end and a distal end. The distal end may be embedded in bone with the proximal end exposed. An abutment surface is disposed toward the proximal end. The anchoring element includes four surfaces that define the distal end. A generally cylindrical first surface defines an exterior of the anchoring element and includes a first external thread having a pitch. An annular second surface is disposed toward the distal end and joined to the first surface along an outer circumference of the second surface. A third surface concentric with the first surface is joined to the second surface along an inner circumference of the second surface. A fourth surface disposed between the distal end and the proximal end of the first surface is joined to the third surface along an outer circumference of the fourth surface.